


AN1V PB20

Current Sensor

Model Number:

AN1V 50 PB20
 AN1V 100 PB20
 AN1V 150 PB20
 AN1V 200 PB20



For the electronic measurement of current:DC,AC,pulsed...,with galvanic separation between the primary and the secondary circuit.

Features

- ❖ Open loop current sensor using the Hall effect.
- ❖ ASIC Technology.
- ❖ Maintain output proportional to changes in the power supply (include offset and sensitivity) .
- ❖ Galvanic separation between primary and secondary.
- ❖ Insulating plastic case recognized according to UL 94-V0.
- ❖ No insertion losses.
- ❖ Small size.
- ❖ Standards:
 - IEC 60664-1:2020
 - IEC 61800-5-1:2022
 - IEC 62109-1:2010

Applications

- ❖ AC variable speed.
- ❖ Uninterruptible Power Supply (UPS).
- ❖ Static converters for DC motor drives.
- ❖ Switch Mode Power Supplies (SMPS).
- ❖ Power supply for welding applications.
- ❖ Battery Management.
- ❖ Wind energy inverter.

Safety

The sensor must be used according to IEC 61800-5-1.

The sensor must be used in electric/electronic equipment with respect to applicable standards and safety requirements in accordance with the following manufacturer's operating instructions.

Caution, risk of electrical shock !



When operating the sensor, certain parts of the module can carry hazardous voltage (e.g., Primary busbar, power supply). Ignore this warning can lead to injury and/or cause serious damage.

This sensor is a built-in device, whose conducting parts must be inaccessible after installation. A protective housing or additional shield could be used.

Main supply must be able to be disconnected.

AN1V PB20

Absolute maximum ratings(not operating)

Parameter	Symbol	Unit	Value
Supply voltage	V_C	V	6.5
ESD rating, Human Body Model (HBM)	V_{ESD}	V	8000

※ Stresses above these ratings may cause permanent damage.

※ Exposure to absolute maximum ratings for extended periods may degrade reliability.

Environmental and mechanical characteristics

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Ambient operating temperature	T_A	°C	-40 -40 -40 -40		150 150 125 85	AN1V 50 PB20 AN1V 100 PB20 AN1V 150 PB20 AN1V 200 PB20
Ambient storage temperature	T_S	°C	-55		150	
Primary resistance value	R_P	$\mu\Omega$		100		
Mass	m	g		5		

Insulation coordination

Parameter	Symbol	Unit	Value	Comment
Rms voltage for AC insulation test, @50Hz,1min	V_d	kV	4.8	According to IEC 60664-1
Plastic case	-	-	UL94-V0	
Comparative tracking index	CTI	PLC	2	
Application example	-	-	475V _{RMS}	Reinforced insulation,according to IEC 61800-5-1, IEC 62109-1CATIII, PD2
Application example	-	-	960V _{RMS}	Basic insulation,according to IEC 61800-5-1, IEC 62109-1CATIII, PD2

AN1V PB20

Electrical data

AN1V 50 PB20

※ With $T_A = 25^\circ\text{C}$, $V_C = 5\text{V}$, $R_L = 10\text{k}\Omega$, unless otherwise noted.

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Electrical data						
Primary nominal rms current	I_{PN}	A	-50		50	
Supply voltage	V_C	V	4.5	5.0	5.5	
Output voltage	V_{OUT}	V	$V_{OUT} = V_{QOV} + G_{th} \times I_P \times (V_C/5)$			
Electrical offset voltage	V_{QOV}	V		$V_{CC}/2$		
Theoretical sensitivity	G_{th}	mV/A		40		
Current consumption	I_C	mA		8	11	
Load resistance	R_L	kΩ	5.1			
Load capacitor	C_2	nF		1	10	
Power filter capacitor	C_1	nF		100		
Performance data						
Sensitivity error	\mathcal{E}_G	%	-1		1	
Temperature of G	TCG	%	-1.5		1.5	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Electrical offset current	V_{OE}	mV	-10	±5	10	@ $V_C = 5\text{V}$ also $I_P = 0\text{A}$
Electrical offset error of temperature drift	TCV_{OE}	mV	-10		10	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Hysteresis offset voltage	V_{OM}	mV		4		@ $V_C = 5\text{V}$, after $\pm I_{PN}$
Linearity error	\mathcal{E}_L	% of I_{PN}	-1		1	Exclusive of V_{OE}
Accuracy @ I_{PN}	X	% of I_{PN}	-2		2	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Response time @90% of I_{PN}	t_r	μs		2.5	5	@ $C_2 = 1\text{nF}$
Frequency bandwidth(-3dB)	BW	kHz		250		@ $C_2 = 1\text{nF}$
Output noise	V_{no}	mV		5		@ $C_2 = 1\text{nF}$

AN1V PB20

Electrical data

AN1V 100 PB20

※ With $T_A = 25^\circ\text{C}$, $V_C = 5\text{V}$, $R_L = 10\text{k}\Omega$, unless otherwise noted.

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Electrical data						
Primary nominal rms current	I_{PN}	A	-100		100	
Supply voltage	V_C	V	4.5	5.0	5.5	
Output voltage	V_{OUT}	V	$V_{OUT} = V_{QOV} + G_{th} \times I_P \times (V_C/5)$			
Electrical offset voltage	V_{QOV}	V		$V_{CC}/2$		
Theoretical sensitivity	G_{th}	mV/A		20		
Current consumption	I_C	mA		8	11	
Load resistance	R_L	kΩ	5.1			
Load capacitor	C_2	nF		1	10	
Power filter capacitor	C_1	nF		100		
Performance data						
Sensitivity error	\mathcal{E}_G	%	-1		1	
Temperature of G	TCG	%	-1.5		1.5	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Electrical offset current	V_{OE}	mV	-10	±5	10	@ $V_C = 5\text{V}$ also $I_P = 0\text{A}$
Electrical offset error of temperature drift	TCV_{OE}	mV	-10		10	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Hysteresis offset voltage	V_{OM}	mV		4		@ $V_C = 5\text{V}$, after $\pm I_{PN}$
Linearity error	\mathcal{E}_L	% of I_{PN}	-1		1	Exclusive of V_{OE}
Accuracy @ I_{PN}	X	% of I_{PN}	-2		2	@ $T_A = -40^\circ\text{C} \sim 150^\circ\text{C}$
Response time @90% of I_{PN}	t_r	μs		2.5	5	@ $C_2 = 1\text{nF}$
Frequency bandwidth(-3dB)	BW	kHz		250		@ $C_2 = 1\text{nF}$
Output noise	V_{no}	mV		2.7		@ $C_2 = 1\text{nF}$

Electrical data

AN1V 150 PB20

※ With $T_A = 25^\circ\text{C}$, $V_C = 5\text{V}$, $R_L = 10\text{k}\Omega$, unless otherwise noted.

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Electrical data						
Primary nominal rms current	I_{PN}	A	-150		150	
Supply voltage	V_C	V	4.5	5.0	5.5	
Output voltage	V_{OUT}	V	$V_{OUT} = V_{QOV} + G_{th} \times I_P \times (V_C/5)$			
Electrical offset voltage	V_{QOV}	V		$V_{CC}/2$		
Theoretical sensitivity	G_{th}	mV/A		13.33		
Current consumption	I_C	mA		8	11	
Load resistance	R_L	kΩ	5.1			
Load capacitor	C_2	nF		1	10	
Power filter capacitor	C_1	nF		100		
Performance data						
Sensitivity error	\mathcal{E}_G	%	-1		1	
Temperature of G	TCG	%	-1.5		1.5	@ $T_A = -40^\circ\text{C} \sim 125^\circ\text{C}$
Electrical offset current	V_{OE}	mV	-10	±5	10	@ $V_C = 5\text{V}$ also $I_P = 0\text{A}$
Electrical offset error of temperature drift	TCV_{OE}	mV	-10		10	@ $T_A = -40^\circ\text{C} \sim 125^\circ\text{C}$
Hysteresis offset voltage	V_{OM}	mV		4		@ $V_C = 5\text{V}$, after $\pm I_{PN}$
Linearity error	\mathcal{E}_L	% of I_{PN}	-1		1	Exclusive of V_{OE}
Accuracy@ I_{PN}	X	% of I_{PN}	-2		2	@ $T_A = -40^\circ\text{C} \sim 125^\circ\text{C}$
Response time@ 90% of I_{PN}	t_r	μs		2.5	5	@ $C_2 = 1\text{nF}$
Frequency bandwidth(-3dB)	BW	kHz		250		@ $C_2 = 1\text{nF}$
Output noise	V_{no}	mV		1.8		@ $C_2 = 1\text{nF}$

AN1V PB20

Electrical data


AN1V 200 PB20

※ With $T_A = 25^\circ\text{C}$, $V_C = 5\text{V}$, $R_L = 10\text{k}\Omega$, unless otherwise noted.

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Electrical data						
Primary nominal rms current	I_{PN}	A	-200		200	
Supply voltage	V_C	V	4.5	5.0	5.5	
Output voltage	V_{OUT}	V	$V_{OUT} = V_{QOV} + G_{th} \times I_P \times (V_C/5)$			
Electrical offset voltage	V_{QOV}	V		$V_{CC}/2$		
Theoretical sensitivity	G_{th}	mV/A		10		
Current consumption	I_C	mA		8	11	
Load resistance	R_L	kΩ	5.1			
Load capacitor	C_2	nF		1	10	
Power filter capacitor	C_1	nF		100		
Performance data						
Sensitivity error	\mathcal{E}_G	%	-1		1	
Temperature of G	TCG	%	-1.5		1.5	@ $T_A = -40^\circ\text{C} \sim 85^\circ\text{C}$
Electrical offset current	V_{OE}	mV	-10	±5	10	@ $V_C = 5\text{V}$ also $I_P = 0\text{A}$
Electrical offset error of temperature drift	TCV_{OE}	mV	-10		10	@ $T_A = -40^\circ\text{C} \sim 85^\circ\text{C}$
Hysteresis offset voltage	V_{OM}	mV		4		@ $V_C = 5\text{V}$, after $\pm I_{PN}$
Linearity error	\mathcal{E}_L	% of I_{PN}	-1		1	Exclusive of V_{OE}
Accuracy@ I_{PN}	X	% of I_{PN}	-2		2	@ $T_A = -40^\circ\text{C} \sim 85^\circ\text{C}$
Response time@ 90% of I_{PN}	t_r	μs		2.5	5	@ $C_2 = 1\text{nF}$
Frequency bandwidth(-3dB)	BW	kHz		250		@ $C_2 = 1\text{nF}$
Output noise	V_{no}	mV		1.4		@ $C_2 = 1\text{nF}$

AN1V PB20

Dimensions(Unit mm)



Recommeng PCB layout

Mechanical characteristics

- ◊ General tolerance ±0.3 mm
- ◊ Conductor and pin material Red copper with tin plating

Remarks

- ◊ When I_P flows in the direction of pin4 to pin5, V_{out} increase.